

INNOVATION IN SILICON CARBIDE

SIKA® ABR



KYMERA INTERNATIONAL

High-quality silicon carbide for abrasive applications

Kymera International is the world's leading producer of silicon carbide. Based on long time experience and industrial expertise, we are delighted to provide a wide range of high quality products combined with excellent

Together with our customers we are expanding in growing markets by increasing our production and processing capacities. Environmental protection and safety aspects are crucial for us, which we continuously develop by optimizing our production processes. Due to its high abrasion resistance and relatively low cost, silicon carbide is, in many different forms, used as a loose- or fixed-abrasive material in a wide variety of applications:

- Grinding wheels with organic or vitrified bonds
- Honing sticks
- Cut-off and thin wheels
- Snagging wheels
- Stone polishing segments
- Coated abrasive sheets, belts and discs
- Non-woven abrasive
- Lapping and polishing of substrates and mechanical components
- Surface blasting
- Anti-slip flooring

Our long experience in serving leading manufacturers in the abrasives industry, from our many local production platforms, allows us to have a deep understanding of our Abrasive customers' requirements.

In addition to our broad product range, we have the capability to co-develop with our clients new tailormade solutions.

Properties of silicon carbide

SiC is a ceramic material with an outstanding hardness, only surpassed by diamond, cubic boron nitride and boron carbide. The material is highly wear-resistant and chemically inert to all alkalis as well as acids. It can also withstand very high temperatures. These properties make silicon carbide an outstanding abrasive and ceramic material to be used under extreme operating

Silicon carbide abrasives are ideal for grinding low tensile materials like grey iron and unannealed malleable iron, non-metallic materials such as stone, ceramic, glass, plastic and rubber. Silicon carbide is also used for non-ferrous material, cast iron and stainless steel.





Each particular product in our wide range of solutions is adapted to the customer needs, and is characterized by the following parameters:

Particle size distribution

All micro and macro grit sizes according to FEPA,

JIS, and ANSI standards

Particle shape

Blocky or sharp-shape grits

Crystal grade

Green and black silicon carbide

Surface chemistry

Various purity levels
dependent on the type of
treatment:
chemically-treated,
water-washed,
air-dusted

Density

3,21 g/cm³

Vickers Hardness

29 GPa

Coefficient of thermal expansion

5-10⁻⁶ K

Thermal conductivity

50 to 100 W/m K

Temperature resistance

1500 °C in air, **2400 °C** in inert atmosphere



SIKA® ABR **Characteristics & Color** Classification **Grit Sizes** Description MAC + MIC F24 - F220, produced to comply with FEPA standard and high purity green silicon F230 - F2000 carbide particulary suitable for high quality vitrified and resin bonded grinding wheels, honing stones, lapping and polishing applications high quality green silicon MAC + MIC F16 - F220, produced to comply with FEPA standard and F230 - F1200 carbide particularly suitable for vitrified and resin bonded grinding wheels, honing stones and polishing applications MAC + MIC F8 - F220, produced to comply with FEPA standard and IΙΑ green silicon carbide F230 - F800 particularly suitable for vitrified and resin bonded grinding wheels, honing stones and polishing applications high purity black silicon MAC + MIC F24 - F220, produced to comply with FEPA standard and carbide F230 - F2000 particularly suitable for high quality vitrified or resin bonded grinding wheels, lapping and polishing applications IIIL MIC produced to comply with FEPA standard and special grains in black F400L - 800L silicon carbide for lapping particularly suitable for lapping applications. Special designed grains enable smooth surface finish without scratches or cracks IV high quality black silicon MAC + MIC F8 - F220, produced to comply with FEPA standard and F230 - F1200 carbide particularly suitable for high quality resinoid bonded grinding wheels, cut-off oder snagging wheels, flap-discs and anti-slip flooring applications black silicon carbide MAC F8 - F220, produced to comply with FEPA standard F240 - F800 and particularly suitable for resinoid bonded grinding wheels, cut-off or snagging wheels, anti-slip flooring applications P8 - P5000 high quality black silicon MAC + MIC produced to comply with FEPA standard carbide and particularly suitable for high quality coated abrasives for surface preparation and finishing high quality black silicon MIC F230 - F600 produced to comply with FEPA standard carbide and particularly suitable for stone polishing applications

EXCELLENT PROPERTIES FOR HIGH PERFORMANCE ABRASIVE APPLICATIONS

Products for bonded abrasive – Vitrified bond (glass)

Products for bonded abrasive – Organic bond (resin, rubber, plastic)

Color

green

green

black

black

SIKA® ABR	Grit Sizes	Color	SIKA® ABR	Grit Sizes
1	F24 - F2000	green	1	F16 - F1200
II	F16 - F1200	green	IIA	F16 - F800
III	F24 - F2000	black	IV	F8 - F1200
IV	F8 - F1200	black	IV A	F8 - F800

Products for stone polishing

Products for lapping and polishing

SIKA® ABR	Grit Sizes	Color
IV A	F8 - F800	black
IV	F8 - F220	black
Stone	F240 - F600	black

SIKA® ABR	Grit Sizes	Color
1	F8 - F2000	green
III	F230 - F2000	black
III L	F400L - F1000L	black

Products for flooring

Products for blasting

	SIKA® ABR	Grit Sizes	Color
Ī	IV A	F8 – F40	black
	IV	F8 - F40	black

SIKA® ABR	Grit Sizes	Color
IV A	F8 - F220	black
IV	F8 - F220	black

Products for coated abrasive

SIKA® ABR	Grit Sizes	Color
Р	P8 - P5000	black

6 | SIKA ABR | 7

Products for abrasives and ceramic grains

SIKA® ABR I and II green SiC FEPA-F and JIS, SIKA® ABR III and IV black SiC FEPA-F-P and JIS

Macro Sizes			Macro Sizes						
	ASTM	М	edian value	of		ASTM	М	edian value	of
μm	mesh	F	Р	JIS	μm	mesh	F	Р	JIS
63		220		220	450		40		40
65			220		500	35			
75	200	180		180	525			36	
80			180		530		36		36
90	170	150		150	600	30			
98			150		625			30	
106	140				630		30		30
110		120		120	710	25			
120			120		740			24	
125	120				750		24		24
130		100		100	850	20			
150	100				880		22		22
155		90		90	980			20	
160			100		mm				
180	80				1.00	18			
190		80		80	1.04		20		20
200			80		1.18	16			
212	70				1.25		16		16
220		70		70	1.30			16	
250	60				1.40	14			
260			60		1.48		14		14
270		60		60	1.70	12			
300	50				1.75		12	12	12
320		54		54	2.00	10			
330			50		2.10		10		10
355	45				2.36	8			
390		46		46	2.50		8		8
415			40		2.80	7			
425	40				3.35	6			

Products for abrasives and ceramic grains

Apertures for ASTM sieve and the 50% point for F-P and JIS grits

		licro Size	s			
Median value of						
μm	ASTM mesh	F	Р	JIS		
0.4				10000		
0.7				9000		
1.2		2000		8000		
2.0		1500		6000		
2.7			5000			
3.0		1200		4000		
3.6			4000			
4.0				3000		
4.5		1000	3000			
5.4			2500			
5.5				2500		
6.5		800	2000			
6.7				2000		
8.0				1500		
8.6			1500			
9.3		600				
9.5				1200		
11.5				1000		
12.8		500				
14.0				800		
15.3			1200			
17.0				700		
17.3		400				
18.3			1000			
20.0				600		
21.8			800			
22.8		360				
25.0				500		

600

Micro Sizes						
	ASTM	Median value of				
μm	mesh	F	Р	JIS		
29.2		320				
30.0				400		
30.2			500			
35.0			400	360		
36.5		280				
38.0	400					
40.0				320		
40.5			360			
44.5		240				
45.0	325					
46.2			320			
48.0				280		
52.2			280			
53.0	270	230				
57.0				240		
58.5			240			

8 | SIKA ABR | 9

25.8

Regional Offices and Contacts

Headquarter (Norway) Fiven AS

Apotekergata 10, 0180 Oslo, Norway

Europe

Belgium

Matériaux Céramiques SA Route de Villers 19 B-4162 Hody Belgium

Customer Service:

Phone: +32 4 383 98 20

Mail: order.be@kymerainternational.com

Germany

Fiven GmbH Gertrudenstraße 30-36 DE-50667 Cologne Germany

Phone: +49 221 6507 6097

Mail: sika_emea@kymerainternational.com

Web: www.fiven.com

Norway

Fiven Norge AS P.O. Box 113 N-4790 & N-4792 Lillesand Norway

Customer Service:

Phone: +47 372 60 000

Mail: order.no@kymerainternational.com

South America

Brazil

Carbeto de Silício SIKA Brasil Rod. Br 265 km, km 208-Zona Rural 36202-630 Barbacena-Minas Gerais-MG Brazil

Customer Service:

Phone: +55 32 3339 1700

Mail: sika_sa@kymerainternational.com

North America

The United States

FIVEN North America, Inc. 651 Holiday Drive Plaza 5 – Suite 400 Pittsburgh, PA 15220

Sales

Phone: +1 (412) 706-1544

Mail: sika_na@kymerainternational.com

Asia

China

Fiven AS
Room 329, F-space, 198 Le Yuan Road,
Pu Dong new district 201206,
Shanghai
China

Mobile: +86 139 17729448

Mail: jack.zhong@kymerainternational.com

10 | REGIONAL OFFICES AND CONTACTS | 11



Join us on the fiven.com website

Follow us on social networks



